



**WAGO START MODULE FOR 1-CONDUCTOR FEMALE CONNECTOR; WITH
INTEGRATED END PLATE; 2.5 MM²; 1-POLE; 2,50 MM²; ORANGE**

Ratings per: IEC/EN 61984;

Tensiune nominala (III/3): 690; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Curent nominal 2: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar poli: 1;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Latime: 5,2 mm / 0.205 inch;

Inaltime: 40,5 mm / 1.594 inch;

Adancime: 22,4 mm / 0.882 inch;

Marking level: Side marking;

Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductor;
Culoare: orange;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,06; MJ
Greutate: 3,4; g
Product Group: 18 (X-COM-System);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4050821243328;
Customs tariff number: 85366990990;
Pret: 7,11 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/start-module-for-1-conductor-female-connector-with-integrated-end-plate-2-5-mm2-1-pole-2-50-mm2-orange-146464>