



**WAGO 1-CONDUCTOR MALE CONNECTOR; SNAP-IN FLANGE; 4 MM²; PIN SPACING
5 MM; 15-POLE; 4,00 MM²; GRAY**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm²;

Solid conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 15;

Numar total de conexiuni: 15;

Total number of potentials: 15;

Wiring type: Front-entry wiring;

Distanta intre pini: 5 mm / 0.197 inch;

Latime: 96,3 mm / 3.791 inch;

Inaltime: 24,4 mm / 0.961 inch;

Adancime: 40,8 mm / 1.606 inch;

Tip montaj: Snap-in;

Tip contact (pluggable connector): Conector tata/fisa;

Connector (connection type): for conductor;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,906; MJ

Greutate: 45,2; g

Product Group: 18 (X-COM-System);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4044918854559;
Customs tariff number: 85366990990;
Pret: 58,08 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-male-connector-snap-in-flange-4-mm2-pin-spacing-5-mm-15-pole-4-00-mm2-gray-146514>