



**WAGO TESTING PLUG MODULE WITH CONTACT STUD; PIN SPACING 5.08 MM / 0.2 IN; 2,50 MM<sup>2</sup>; ORANGE**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/2): 250; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Curent nominal: 0,5; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Certificari: UL 1059;

Tehnologie conexiune: CAGE CLAMP®;

Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Numar tipuri de conexiuni: 1;

Distanta intre pini: 5.08 mm / 0.2 inch;

Latime: 5.08 mm / 0.2 inch;

Inaltime: 14.3 mm / 0.563 inch;

Adancime: 44.45 mm / 1.75 inch;

Test contact length: 18; mm

Application: Testing wired terminal blocks with 0.75 ... 1.5 mm<sup>2</sup> "f-st" or 0.5 mm<sup>2</sup> "sol." conductors;

Suitable: for 736, 737, 738 Series;

Culoare: orange;

Material group: I;

Material izolator: Polyamide 66 (PA 66);

Flammability class per UL94: V0;

Clamping spring material: Chrome nickel spring steel (CrNi);

Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;  
Fire load: 0,024; MJ  
Greutate: 1,9; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 3 (Multi Conn. System);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454761950;  
Customs tariff number: 85366990990;  
Pret: 19,42 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/testing-plug-module-with-contact-stud-pin-spacing-5-08-mm-0-2-in-2-50-mm2-orange-147529>