



**WAGO TESTING PLUG MODULE WITH CONTACT STUD; PIN SPACING 7.62 MM / 0.3 IN; 2,50 MM<sup>2</sup>; ORANGE**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/2): 250; V  
Tensiune nominala de supratensiune (III/2): 2,5; kV  
Curent nominal: 0,5; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Tehnologie conexiune: CAGE CLAMP®;  
Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;  
Numar total de conexiuni: 1;  
Total number of potentials: 1;  
Numar tipuri de conexiuni: 1;  
Distanta intre pini: 7.62 mm / 0.3 inch;  
Latime: 7.62 mm / 0.3 inch;  
Inaltime: 14.3 mm / 0.563 inch;  
Adancime: 36.45 mm / 1.435 inch;  
Test contact length: 10; mm  
Application: Testing unwired terminal blocks;  
Suitable: for 236 Series;  
Culoare: orange;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;  
Fire load: 0,035; MJ  
Greutate: 2,2; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 3 (Multi Conn. System);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454761905;  
Customs tariff number: 85366990990;  
Pret: 19,42 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/testing-plug-module-with-contact-stud-pin-spacing-7-62-mm-0-3-in-2-50-mm2-orange-149786>