



**WAGO BOARD-TO-BOARD LINK; PIN SPACING 6.5 MM; LENGTH: 15.6 MM**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Tensiune nominala (III/2): 320; V  
Tensiune nominala de supratensiune (III/2): 4; kV  
Tensiune nominala (II/2): 630; V  
Tensiune nominala de supratensiune (II/2): 4; kV  
Curent nominal: 9; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Numar tipuri de conexiuni: 1;  
Adancime: 15,6 mm / 0.614 inch;  
Length: 15,6; mm  
Length: 15,6; mm  
Diameter: 1; mm  
Diameter: 1; mm  
Mating cycles (max.): 10;  
Number of mating cycles: max. 10 connections/disconnections;  
Suitable: for SMD PCB Terminal Blocks; 2065 Series;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Contact material: Copper alloy;  
Contact plating: tin-plated;  
Greutate: 0,1; g  
Temperatura lucru: -60 ... +120 °C;  
Tip ambalare: BOX;  
Tara de origine: DE;

GTIN: 4055143862721;  
Customs tariff number: 85369010000;  
Pret: 0,55 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/board-to-board-link-pin-spacing-6-5-mm-length-15-6-mm-150063>