



WAGO 1-CONDUCTOR FEMALE PLUG; 2.5 MM²; 5-POLE; 2,50 MM²; GREEN-YELLOW, BLUE, GRAY

Ratings per: IEC/EN 61984;

Tensiune nominala (III/3): 690; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 20; A

Curent nominal 2: 32; A

Tensiune nominala EN (Ex e II): 630; V

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 2.5 mm²;

Solid conductor: 0.25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0.75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0.25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2.5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2.5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar poli: 5;

Numar total de conexiuni: 5;

Total number of potentials: 5;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 26 mm / 1.024 inch;

Inaltime: 40.5 mm / 1.594 inch;

Adancime: 22.4 mm / 0.882 inch;

Module Latime: 5.2 mm / 0.205 inch;

Marking level: Side marking;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductors;
Culoare: green-yellow, blue, gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 16,5; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143534413;
Customs tariff number: 85366990990;
Pret: 39,82 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-female-plug-2-5-mm2-5-pole-2-50-mm2-green-yellow-blue-gray-150125>