



**WAGO COMPONENT TERMINAL BLOCK; 4-CONDUCTOR; LED (RED); 24 VDC; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 1.5 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 1,50 MM<sup>2</sup>; GRAY**

Voltage type 1: DC;

Tensiune nominala: 24; V

Ratings per: IEC/EN 60947-7-1;

Curent nominal: 0,025; A

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 15; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 1.5 mm<sup>2</sup>;

Solid conductor: 0.25 ... 2.5 mm<sup>2</sup> / 22 ... 14 AWG;

Solid conductor; push-in termination: 0.75 ... 2.5 mm<sup>2</sup> / 18 ... 14 AWG;

Fine-stranded conductor: 0.25 ... 2.5 mm<sup>2</sup> / 22 ... 14 AWG;

Fine-stranded conductor; with insulated ferrule: 0.75 ... 1.5 mm<sup>2</sup> / 18 ... 16 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0.75 ... 1.5 mm<sup>2</sup> / 18 ... 16 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar total de conexiuni: 4;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 4.2 mm / 0.165 inch;

Inaltime from upper-edge of DIN-rail: 32.9 mm / 1.295 inch;

Adancime: 69.9 mm / 2.752 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Greutate: 6,1; g

Product Group: 22 (TOPJOB S);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4045454537623;

Customs tariff number: 85369010000;

Pret: 37,07 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/component-terminal-block-4-conductor-led-red-24-vdc-for-din-rail-35-x-15-and-35-x-7-5-1-5-mm2-push-in-cage-clamp-1-50-mm2-gray-150513>