www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO FEEDTHROUGH TERMINAL BLOCK; CONDUCTOR/WIRE-WRAP CONNECTION; PLATE THICKNESS: 1.5 MM; 4 MM²; PIN SPACING 6 MM; 1-POLE; CAGE CLAMP®; 4,00 MM²; GRAY

Ratings per: IEC/EN 60664-1;
Ratings (note): Wire-wrap pin;
Tesiune nominala (III/3): 320; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tesiune nominala (II/2): 630; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 4; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 4; A
Tensiune nominala UL (Use Group C): 300; V
Curent nominal UL (Use Group C): 4; A
Tensiune nominala UL (Use Group D): 600; V
Curent nominal UL (Use Group D): 4; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 300; V
Curent nominal CSA (Use Group B): 4; A
Tensiune nominala CSA (Use Group C): 300; V
Curent nominal CSA (Use Group C): 4; A
Tensiune nominala CSA (Use Group D): 600; V
Curent nominal CSA (Use Group D): 4; A
Tehnologie conexiune: CAGE CLAMP®;
Number of connection points (connection type): 1;

Tip actionare: Operating tool;
Solid conductor: 0,08 … 4 mm² / 28 … 12 AWG;
Fine-stranded conductor: 0,08 … 4 mm² / 28 … 12 AWG;
Fine-stranded conductor; with insulated ferrule: 0,25 … 2,5 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0,25 … 2,5 mm²;
Strip length: 9 … 10 mm / 0.35 … 0.39 inch;
Numar poli: 1;
Tehnologie conexiune 2: Wire-wrap pin;
Number of connection points: 1;
Numar total de conexiuni: 1;
Total number of potentials: 1;
Numar tipuri de conexiuni: 2;
Numar nivele: 1;
Distanta intre pini: 6 mm / 0.236 inch;
Latime: 6 mm / 0.236 inch;
Inaltime: 38,5 mm / 1.516 inch;
Inaltime de la fata: 22 mm / 0.866 inch;
Adancime: 26 mm / 1.024 inch;
Housing sheet thickness: 1,5 … 1,5 mm / 0.059 … 0.059 inch;
Tip montaj: Snap-in mounting foot;
Tip montaj: Feed-through mounting;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 3,4; g
Temperatura lucru: -60 … +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4045454071677;
Customs tariff number: 85369010000;
Pret: 15,03 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/feedthrough-terminal-block-conductor-wire-wrap-connection-plate-thickness-1-5-mm-4-mm2-pin-spacing-6-mm-1-pole-cage-clamp-4-00-mm2-gray-150618