



WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 185 MM²; SUITABLE FOR EX E II APPLICATIONS; LATERAL MARKER SLOTS; ONLY FOR DIN 35 X 15 RAIL; POWER CAGE CLAMP; 185,00 MM²; LIGHT GRAY

Ratings per: IEC/EN 60947-7-1;
Tensiune nominala EN (Ex e II): 1.000; V
Curent nominal (Ex e II) with jumper: 250; A
Tehnologie conexiune: POWER CAGE CLAMP;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Nominal cross-section: 185 mm²;
Solid conductor: 50 ... 185 mm² / 1/0 AWG ... 350 kcmil;
Stranded conductor: 50 ... 185 mm² / 1/0 AWG ... 350 kcmil;
Fine-stranded conductor: 50 ... 185 mm² / 1/0 AWG ... 350 kcmil;
Fine-stranded conductor; with insulated ferrule: 50 ... 150 mm² / 1/0 AWG ... 300 kcmil;
Fine-stranded conductor; with uninsulated ferrule: 50 ... 185 mm² / 1/0 AWG ... 350 kcmil;
Strip length: 45 ... 47 mm / 1.77 ... 1.85 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 32 mm / 1.26 inch;
Inaltime from upper-edge of DIN-rail: 116 mm / 4.567 inch;
Adancime: 133 mm / 5.236 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Side marking;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);

Greutate: 534,9; g
Product Group: 1 (Rail Mounted Terminal Blocks);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143067089;
Customs tariff number: 85369010000;
Pret: 274,52 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-185-mm2-suitable-for-ex-e-ii-applications-lateral-marker-slots-only-for-din-35-x-15-rail-power-cage-clamp-185-00-mm2-light-gray-150689>