



**WAGO FEEDTHROUGH TERMINAL BLOCK; CONDUCTOR/WIRE-WRAP CONNECTION; PLATE THICKNESS: 1.5 MM; 4 MM<sup>2</sup>; PIN SPACING 6 MM; 1-POLE; CAGE CLAMP®; 4,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60664-1;

Ratings (note): Wire-wrap pin;

Tensiune nominala (III/3): 320; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 4; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 4; A

Tensiune nominala UL (Use Group C): 300; V

Curent nominal UL (Use Group C): 4; A

Tensiune nominala UL (Use Group D): 600; V

Curent nominal UL (Use Group D): 4; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 4; A

Tensiune nominala CSA (Use Group C): 300; V

Curent nominal CSA (Use Group C): 4; A

Tensiune nominala CSA (Use Group D): 600; V

Curent nominal CSA (Use Group D): 4; A

Tehnologie conexiune: CAGE CLAMP®;

Number of connection points (connection type): 1;

Tip actionare: Operating tool;  
Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor; with insulated ferrule: 0,25 ... 2,5 mm<sup>2</sup>;  
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 2,5 mm<sup>2</sup>;  
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;  
Numar poli: 1;  
Tehnologie conexiune 2: Wire-wrap pin;  
Number of connection points: 1;  
Numar total de conexiuni: 1;  
Total number of potentials: 1;  
Numar tipuri de conexiuni: 2;  
Numar nivele: 1;  
Distanta intre pini: 6 mm / 0.236 inch;  
Latime: 6 mm / 0.236 inch;  
Inaltime: 38,5 mm / 1.516 inch;  
Inaltime de la fata: 22 mm / 0.866 inch;  
Adancime: 26 mm / 1.024 inch;  
Housing sheet thickness: 2,5 ... 2,5 mm / 0.098 ... 0.098 inch;  
Tip montaj: Snap-in mounting foot;  
Tip montaj: Feed-through mounting;  
Culoare: gray;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Greutate: 3,4; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 4 (Printed Circuit);  
Tip ambalare: bag;  
Tara de origine: DE;  
GTIN: 4045454069186;  
Customs tariff number: 85369010000;  
Pret: 14,89 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/feedthrough-terminal-block-conductor-wire-wrap-connection-plate-thickness-1-5-mm-4-mm2-pin-spacing-6-mm-1-pole-cage-clamp-4-00-mm2-gray-150805>