



**WAGO THREE PHASE SET; WITH 185 MM<sup>2</sup> HIGH-CURRENT TERMINAL BLOCK;  
WITH FIXING FLANGES; COPPER; 185 MM<sup>2</sup>; POWER CAGE CLAMP; 185,00 MM<sup>2</sup>;  
MULTICOLOURED**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 1000; V

Tensiune nominala de supratensiune (III/3): 12; kV

Tensiune nominala (III/3) 2: 1500; V

Tensiune nominala de supratensiune (III/3) 2: 12; kV

Tehnologie conexiune: POWER CAGE CLAMP;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Nominal cross-section: 185 mm<sup>2</sup>;

Solid conductor: 50 ... 185 mm<sup>2</sup> / 1/0 AWG ... 350 kcmil;

Stranded conductor: 50 ... 185 mm<sup>2</sup> / 1/0 AWG ... 350 kcmil;

Fine-stranded conductor: 50 ... 185 mm<sup>2</sup> / 1/0 AWG ... 350 kcmil;

Fine-stranded conductor; with insulated ferrule: 50 ... 150 mm<sup>2</sup> / 1/0 AWG ... 300 kcmil;

Fine-stranded conductor; with uninsulated ferrule: 50 ... 185 mm<sup>2</sup> / 1/0 AWG ... 350 kcmil;

Strip length: 45 ... 47 mm / 1.77 ... 1.85 inch;

Numar total de conexiuni: 10;

Total number of potentials: 4;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Inaltime de la fata: 123 mm / 4.843 inch;

Adancime: 170 mm / 6.693 inch;

Design: horizontal;

Tip montaj: Mounting flange;

Marking level: Side marking;

Culoare: multicoloured;

Material izolator: Polyamide 66 (PA 66);

Greutate: 2217,9; g

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4055143657006;

Customs tariff number: 85369010000;

Pret: 1.080,84 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/three-phase-set-with-185-mm2-high-current-terminal-block-with-fixing-flanges-copper-185-mm2-power-cage-clamp-185-00-mm2-multicoloured-150817>