www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO TRIPLE-DECK TERMINAL BLOCK; THROUGH/THROUGH/THROUGH TERMINAL BLOCK; L/L/L; SUITABLE FOR EX E II APPLICATIONS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; LIGHT GRAY

Ratings per: IEC/EN 60947-7-1;
Curent nominal: 24; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala EN (Ex e II): 420; V
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0.08 … 2.5 mm² / 28 … 12 AWG;
Fine-stranded conductor: 0.08 … 4 mm² / 28 … 12 AWG;
Strip length: 6 … 7 mm / 0.24 … 0.28 inch;
Numar total de conexiuni: 6;
Total number of potentials: 3;
Numar nivele: 3;
Wiring type: Front-entry wiring;
Latime: 5 mm / 0.197 inch;
Inaltime from upper-edge of DIN-rail: 52.5 mm / 2.067 inch;
Adancime: 106 mm / 4.173 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Potential marking: L/L/L;
Marking level: Side marking;
Culoare: light gray;
Fire load: 0,278; MJ
Greutate: 17,5; g
Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4045454129729;
Customs tariff number: 85369010000;
Pret: 19,60 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/triple-deck-terminal-block-through-through-through-terminal-block-l-l-l-suitable-for-ex-e-ii-applications-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-light-gray-150835