



**WAGO 2-CONDUCTOR GROUND TERMINAL BLOCK; 16 MM<sup>2</sup>; SUITABLE FOR EX E  
II APPLICATIONS; LATERAL MARKER SLOTS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5;  
CAGE CLAMP®, 16,00 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Fine-stranded conductor: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Strip length: 16 ... 17 mm / 0.63 ... 0.67 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 12 mm / 0.472 inch;  
Inaltime from upper-edge of DIN-rail: 37,5 mm / 1.476 inch;  
Adancime: 80 mm / 3.15 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking level: Side marking;  
Culoare: green-yellow;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,449; MJ  
Greutate: 42,6; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454088675;  
Customs tariff number: 85369010000;

Pret: 39,64 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-ground-terminal-block-16-mm2-suitable-for-ex-e-ii-applications-lateral-marker-slots-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-16-00-mm2-green-yellow-150965>