



**WAGO 1-CONDUCTOR MALE CONNECTOR; 100% PROTECTED AGAINST
MISMATING; DIN-35 RAIL MOUNTING; 10 MM²; PIN SPACING 7.62 MM; 6-POLE;
10,00 MM²; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 800; V
Tensiune nominala de supratensiune (III/3): 8; kV
Tensiune nominala (III/2): 1000; V
Tensiune nominala de supratensiune (III/2): 8; kV
Tensiune nominala (II/2): 1000; V
Tensiune nominala de supratensiune (II/2): 8; kV
Curent nominal: 41; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group C): 600; V
Curent nominal UL (Use Group C): 42; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group C): 600; V
Curent nominal CSA (Use Group C): 41; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Operating tool;
Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;
Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;
Fine-stranded conductor; with insulated ferrule: 0,5 ... 6 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0,5 ... 6 mm²;
Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;
Numar poli: 6;
Tehnologie conexiune 2: Quick-connect/Solder contact;
Numar total de conexiuni: 6;
Total number of potentials: 6;

Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 7,62 mm / 0.3 inch;
Latime: 47,6 mm / 1.874 inch;
Inaltime from upper-edge of DIN-rail: 34 mm / 1.339 inch;
Adancime: 46 mm / 1.811 inch;
Tip montaj: DIN-35 rail;
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for conductors;
Mismating protection: Yes;
Culoare: light gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,817; MJ
Greutate: 42,8; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 3 (Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454333805;
Customs tariff number: 85366990990;
Pret: 63,23 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-male-connector-100-protected-against-mismating-din-35-rail-mounting-10-mm2-pin-spacing-7-62-mm-6-pole-10-00-mm2-light-gray-150990>