



**WAGO PANEL FEEDTHROUGH MALE CONNECTOR; CLAMPING COLLAR; PIN  
SPACING 5 MM; 5-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Tensiune nominala (III/2): 320; V  
Tensiune nominala de supratensiune (III/2): 4; kV  
Tensiune nominala (II/2): 630; V  
Tensiune nominala de supratensiune (II/2): 4; kV  
Curent nominal: 16; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Tensiune nominala UL (Use Group B): 300; V  
Curent nominal UL (Use Group B): 15; A  
Tensiune nominala UL (Use Group D): 300; V  
Curent nominal UL (Use Group D): 10; A  
Certificari: UL 1059;  
Numar poli: 5;  
Total number of potentials: 5;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Distanta intre pini: 5 mm / 0.197 inch;  
Latime: 39,2 mm / 1.543 inch;  
Inaltime: 14,4 mm / 0.567 inch;  
Adancime: 33,4 mm / 1.315 inch;  
Tip montaj: Mounting flange;  
Tip montaj: Feed-through mounting; Panel mounting;  
Tip contact (pluggable connector): Conector tata/fisa;  
Connector (connection type): for pluggable connector;

Mismating protection: No;  
Locking of plug-in connection: Locking latch;  
Culoare: light gray;  
Material group: I;  
Material izolator: Polyphthalamide (PPA GF);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,104; MJ  
Greutate: 4,9; g  
Temperatura lucru: -60 ... +100 °C;  
Product Group: 26 (picoMAX);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4050821165736;  
Customs tariff number: 85366990990;  
Pret: 15,26 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/panel-feedthrough-male-connector-clamping-collar-pin-spacing-5-mm-5-pole-light-gray-151007>