www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO STACKABLE PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM²; PIN SPACING 3.96 MM; 1-POLE; PUSH-IN CAGE CLAMP®; 1,50 MM²; LIGHT GRAY

Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 200; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tesiune nominala (II/2): 500; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 17,5; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 10; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 10; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 300; V
Curent nominal CSA (Use Group B): 10; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-button;
Solid conductor: 0.5 … 1.5 mm² / 20 … 16 AWG;
Fine-stranded conductor: 0.75 … 1.5 mm² / 20 … 16 AWG;
Fine-stranded conductor; with insulated ferrule: 0.25 … 1 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0.25 … 1 mm²;
Strip length: 9 … 10 mm / 0.35 … 0.39 inch;
Conductor connection direction to PCB: 0; °
Numar poli: 1;
Numar total de conexiuni: 1;

Total number of potentials: 1;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 3.96/4 mm / 0.156/0.157 inch;
Latime: 5.5 mm / 0.217 inch;
Inaltime: 19.1 mm / 0.752 inch;
Inaltime de la fata: 15.5 mm / 0.61 inch;
Adancime: 12.5 mm / 0.492 inch;
Lungimea pinului de contact: 3,6; mm
Solder pin dimensions: 0.4 x 0.8 mm;
Diametrul de gaurire cu toleranta: 1 (+0.1) mm;
PCB contact: THT;
Solder pin arrangement: within the terminal block, in line;
Number of solder pins per potential: 2;
Culoare: light gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,01; MJ
Greutate: 0,6; g
Temperatura lucru: -60 … +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4044918829489;
Customs tariff number: 85369010000;
Pret: 1,48 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/stackable-pcb-terminal-block-push-button-1-5-mm2-pin-spacing-3-96-mm-1-pole-push-in-cage-clamp-1-50-mm2-light-gray-151035