



WAGO 2-CONDUCTOR PCB TERMINAL BLOCK; 10 MM²; PIN SPACING 7.5 MM; 7-POLE; PUSH-IN CAGE CLAMP®; 10,00 MM²; GRAY

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Tensiune nominala (III/2): 1000; V

Tensiune nominala de supratensiune (III/2): 8; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 8; kV

Curent nominal: 50; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 50; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 50; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 600; V

Curent nominal CSA (Use Group B): 44; A

Tensiune nominala CSA (Use Group C): 600; V

Curent nominal CSA (Use Group C): 44; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Operating tool;

Solid conductor: 0.5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor: 0.5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 0.5 ... 6 mm²;

Fine-stranded conductor; with uninsulated ferrule: 0.5 ... 6 mm²;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;

Conductor connection direction to PCB: 45; °

Numar poli: 7;
Numar total de conexiuni: 14;
Total number of potentials: 7;
Numar tipuri de conexiuni: 1;
Numar nivele: 2;
Distanța între pini: 7.5 mm / 0.295 inch;
Latime: 55.2 mm / 2.173 inch;
Inaltime: 41.3 mm / 1.623 inch;
Inaltime de la fata: 36.9 mm / 1.453 inch;
Adancime: 37 mm / 1.457 inch;
Lungimea pinului de contact: 4,4; mm
Solder pin dimensions: 1.6 x 1.2 mm;
Diametrul de gaurire cu toleranta: 2.2 (+0.1) mm;
PCB contact: THT;
Solder pin arrangement: over the entire terminal strip, staggered;
Number of solder pins per potential: 2;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,911; MJ
Greutate: 54,9; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4045454156596;
Customs tariff number: 85369010000;
Pret: 56,55 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-pcb-terminal-block-10-mm2-pin-spacing-7-5-mm-7-pole-push-in-cage-clamp-10-00-mm2-gray-151039>