



**WAGO DOUBLE-DECK TERMINAL BLOCK; THROUGH/THROUGH TERMINAL BLOCK; L/N; WITHOUT MARKER CARRIER; SUITABLE FOR EX E II APPLICATIONS; BLUE CONDUCTOR ENTRY UPPER DECK; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2,5 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 2,50 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Curent nominal 2: 28; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Number of connection points (connection type): 2;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm<sup>2</sup>;

Solid conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Number of connection points: 2;

Numar total de conexiuni: 4;

Total number of potentials: 2;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Latime: 5,2 mm / 0.205 inch;  
Inaltime from upper-edge of DIN-rail: 51,7 mm / 2.035 inch;  
Adancime: 92,5 mm / 3.642 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Potential marking: L/N;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 12,5; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143622516;  
Customs tariff number: 85369010000;  
Pret: 15,01 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/double-deck-terminal-block-through-through-terminal-block-l-n-without-marker-carrier-suitable-for-ex-e-ii-applications-blue-conductor-entry-upper-deck-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-151093>