



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 6 MM<sup>2</sup>; WITH TOUCH-PROOF TEST SOCKET; FOR 4 MM Ø TEST PLUGS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 6,00 MM<sup>2</sup>; BLUE**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 30; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 30; A

Tensiune nominala UL (Use Group C): 300; V

Curent nominal UL (Use Group C): 30; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 30; A

Tensiune nominala CSA (Use Group C): 300; V

Curent nominal CSA (Use Group C): 30; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm<sup>2</sup>;

Solid conductor: 0,5 ... 10 mm<sup>2</sup> / 20 ... 8 AWG;

Solid conductor; push-in termination: 1 ... 10 mm<sup>2</sup> / 14 ... 8 AWG;

Fine-stranded conductor: 0,5 ... 10 mm<sup>2</sup> / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 2,5 ... 6 mm<sup>2</sup> / 16 ... 10 AWG;

Fine-stranded conductor; with uninsulated ferrule: 1,5 ... 6 mm<sup>2</sup> / 16 ... 10 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 2,5 ... 6 mm<sup>2</sup> / 16 ... 17 AWG;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;  
Numar total de conexiuni: 2;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Number of jumper slots: 2;  
Latime: 8 mm / 0.315 inch;  
Inaltime from upper-edge of DIN-rail: 46,8 mm / 1.843 inch;  
Adancime: 99,6 mm / 3.921 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: blue;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 21,9; g  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4055143300285;  
Customs tariff number: 85369010000;  
Pret: 37,36 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-6-mm2-with-touch-proof-test-socket-for-4-mm-oe-test-plugs-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-6-00-mm2-blue-151200>