



**WAGO 2-CONDUCTOR TERMINAL STRIP; 5-POLE; WITHOUT PUSH-BUTTONS;  
WITH SNAP-IN MOUNTING FEET; FOR PLATE THICKNESS 0.6 - 1.2 MM; FIXING  
HOLE 3.5 MM Ø; 1.5 MM<sup>2</sup>; CAGE CLAMP®; 1,50 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 18; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 1,5 mm<sup>2</sup> / 28 ... 16 AWG;

Fine-stranded conductor: 0,08 ... 1,5 mm<sup>2</sup> / 28 ... 16 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 5;

Numar total de conexiuni: 10;

Total number of potentials: 5;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 29,4 mm / 1.157 inch;

Inaltime de la fata: 17 mm / 0.669 inch;

Adancime: 25 mm / 0.984 inch;

Module Latime: 5 mm / 0.197 inch;

Design: horizontal type;

Tip montaj: Snap-in mounting foot;

Marking level: Side marking;

Culoare: gray;

Fire load: 0,176; MJ

Greutate: 9; g

Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918606929;  
Customs tariff number: 85369010000;  
Pret: 11,03 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-terminal-strip-5-pole-without-push-buttons-with-snap-in-mounting-feet-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-1-5-mm2-cage-clamp-1-50-mm2-gray-151217>