



WAGO T-DISTRIBUTION CONNECTOR; 4-POLE; COD. B; 1 INPUT; 2 OUTPUTS; 3 LOCKING LEVERS; FOR FLYING LEADS; PINK

Note on Contact Resistance: approx. 1 m² of contact resistance approx. 0.25 m² contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 25; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 23; A

Numar poli: 4;

Total number of potentials: 4;

Distanta intre pini: 10 mm / 0.394 inch;

Latime: 44 mm / 1.732 inch;

Inaltime: 36,1 mm / 1.421 inch;

Adancime: 48,9 mm / 1.925 inch;

Coding: B;

Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);

Number of mating cycles: ?200, without resistive load 100, with resistive load IN = 25 A, tested (4 mm²/AWG 12);

Distributor type: T-distribution connector;

Marking: 1 2 3 4;

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;

Potential marking: 1 2 3 4;
Suitable: for flying leads;
Tip contact (pluggable connector): Socket/plug;
Mismatching protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: yes;
Culoare: pink;
Material izolator: Polyamide 66 (PA 66);
Contact material: Copper or copper alloy (surface-treated);
Fire load: 0,447; MJ
Greutate: 22,2; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821702184;
Customs tariff number: 85366990990;
Pret: 34,36 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/t-distribution-connector-4-pole-cod-b-1-input-2-outputs-3-locking-levers-for-flying-leads-pink-151273>