www.MATERIALE ELECTRICE.ro
Consiliere specializata



# WAGO 2-CONDUCTOR/2-PIN, DOUBLE-DECK CARRIER TERMINAL BLOCK; 2-CONDUCTOR/2-PIN THROUGH TERMINAL BLOCK; L; INTERNAL COMMONING; CONDUCTOR ENTRY WITH VIOLET MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 1,00 MM²; GRAY

Ratings per: IEC/EN 60947-7-1;
Tesiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 13,5; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 15; A
Tensiune nominala UL (Use Group C): 300; V
Curent nominal UL (Use Group C): 15; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 15; A
Certificari: UL 1059;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Open Tool Slot; Push-in;
Connectable conductor materials: Copper;
Nominal cross-section: 1 mm²;
Solid conductor: 0.14 … 1.5 mm² / 24 … 16 AWG;
Solid conductor; push-in termination: 0.5 … 1.5 mm² / 20 … 16 AWG;
Fine-stranded conductor: 0.14 … 1.5 mm² / 24 … 16 AWG;
Fine-stranded conductor; with insulated ferrule: 0.5 … 0.75 mm² / 20 … 18 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0.5 … 0.75 mm² / 20 … 18 AWG;
Strip length: 9 … 11 mm / 0.35 … 0.43 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;

Numar nivele: 2;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Latime: 3.5 mm / 0.138 inch;
Inaltime from upper-edge of DIN-rail: 51.3 mm / 2.02 inch;
Adancime: 80.1 mm / 3.154 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Potential marking: L;
Marking level: Side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,191; MJ
Greutate: 8,8; g
Product Group: 18 (X-COM-System);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4050821049531;
Customs tariff number: 85366990990;
Pret: 13,73 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/2-conductor-2-pin-double-deck-carrier-terminal-block-2-conductor-2-pin-through-terminal-block-l-internal-commoning-conductor-entry-with-violet-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-1-00-mm2-gray-151330