



WAGO THROUGH-BOARD SMD PCB TERMINAL BLOCK; 0.75 MM²; PIN SPACING 6.5 MM; 3-POLE; PUSH-IN CAGE CLAMP®; IN TAPE-AND-REEL PACKAGING; 0,75 MM²; WHITE

Ratings per: IEC/EN 60664-1;

Ratings (note): Electrical data for FR4 PCB type;

Tensiune nominala (III/3): 320; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 9; A

Ratings per: IEC/EN 60664-1;

Ratings (note) 2: Electrical data for metal-core PCBs;

Tensiune nominala (III/3) 2: 200; V

Tensiune nominala de supratensiune (III/3) 2: 4; kV

Tensiune nominala (III/2) 2: 320; V

Tensiune nominala de supratensiune (III/2) 2: 4; kV

Tensiune nominala (II/2) 2: 500; V

Tensiune nominala de supratensiune (II/2) 2: 4; kV

Curent nominal 2: 9; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Certificari: UL 1059;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 9; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Operating tool;

Solid conductor: 0,2 ... 0,75 mm² / 24 ... 18 AWG;

Fine-stranded conductor: 0,2 ... 0,75 mm² / 24 ... 18 AWG;
Strip length: 8 ... 10 mm / 0.31 ... 0.39 inch;
Conductor connection direction to PCB: 0; °
Numar poli: 3;
Numar total de conexiuni: 3;
Total number of potentials: 3;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 6,5 mm / 0.256 inch;
Latime: 15,8 mm / 0.622 inch;
Inaltime: 7,45 mm / 0.293 inch;
Adancime: 22,2 mm / 0.874 inch;
Reel diameter of tape-and-reel packaging: 330; mm
Tape Latime: 44; mm
Design: with Cover;
Tip montaj: Through-board;
Marking: + - plain;
PCB contact: SMD;
Culoare: white;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper alloy;
Contact plating: tin-plated;
Greutate: 2; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4055143652797;
Customs tariff number: 85369010000;
Pret: 5,01 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/through-board-smd-pcb-terminal-block-0-75-mm2-pin-spacing-6-5-mm-3-pole-push-in-cage-clamp-in-tape-and-reel-packaging-0-75-mm2-white-151342>