



### **WAGO POWER SUPPLY CONNECTOR**

Tensiune nominala (III/2): 400; V  
Tensiune nominala de supratensiune (III/2): 4; kV  
Curent nominal: 18; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Tehnologie conexiune: PUSH WIRE®;  
Solid conductor: 0,5 ... 1,5 mm<sup>2</sup> / 20 ... 16 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar poli: 2;  
Solid conductor 2: 0,5 ... 2,5 mm<sup>2</sup> / 20 ... 14 AWG;  
Numar total de conexiuni: 8;  
Total number of potentials: 2;  
Numar tipuri de conexiuni: 1;  
Latime: 18,5 mm / 0.728 inch;  
Inaltime: 19 mm / 0.748 inch;  
Adancime: 24,5 mm / 0.965 inch;  
Fire load: 0,107; MJ  
Greutate: 6,2; g  
Product Group: 8 (Misc. Chassis Mount Blocks);  
Tip ambalare: bag;  
Tara de origine: PL;  
GTIN: 4044918397094;  
Customs tariff number: 85369010000;  
Pret: 5,88 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/power-supply-connector-151420>