



**WAGO PRE-ASSEMBLED INTERCONNECTING CABLE; CCA; SOCKET/PLUG; 5-
POLE; COD. I; H05Z1Z1-F 5G 1.5 MM²; 6 M; 1,50 MM²; BLUE**

Note on Contact Resistance: approx. 1 m² of contact resistance approx. 0.25 m² contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 23; A

Numar poli: 5;

Total number of potentials: 5;

Ground function: with preceding ground contact;

Conductor preparation: tip-bonded;

Sheathed cable diameter: 9,3 ... 11,6 mm;

Sectiunea transversala a firului: 1,5; mm²

Connection type: Socket - Plug;

Distanta intre pini: 10 mm / 0.394 inch;

Total length: 6; m

Technologie: DALI;

Coding: I;

Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);

Retention force of a plug-in connection: when locked: > 80N;

Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);

Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²);

Connection type: Socket - Plug;

Type of pre-assembled cable: Interconnecting cable;

Cable type: H05Z1Z1-F 5G1.5;
Marking: N ? L DA- DA+;
Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
Potential marking: N ? L DA- DA+;
Application: Lighting management;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Cca;
Contact material: Copper or copper alloy (surface-treated);
Connector Culoare: blue;
Printing color of mating face: white;
Strain relief Culoare: black;
Printing color of strain relief: white;
Sheathed cable Culoare: black;
Printing color of sheathed cable: white;
Halogen-free: Yes;
Greutate: 1114,1; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)
Insulating parts for temperatures ? 105 °C;
Tip ambalare: not packed;
Tara de origine: DE;
GTIN: 4055143817868;
Customs tariff number: 85444290900;
Pret: 246,35 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pre-assembled-interconnecting-cable-cca-socket-plug-5-pole-cod-i-h05z1z1-f-5g-1-5-mm2-6-m-1-50-mm2-blue-151427>