www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 3-CONDUCTOR ACTUATOR SUPPLY TERMINAL BLOCK; LED (YELLOW); FOR PNP-(HIGH-SIDE) SWITCHING ACTUATORS; WITH GROUND CONNECTION VIA PUSH-IN TYPE JUMPER BARS; 1 MM²; PUSH-IN CAGE CLAMP®; 1,00 MM²; GRAY

Voltage type 1: DC;
Tesiune nominala: 24; V
Ratings per: IEC/EN 60947-7-1;
Curent nominal: 13,5; A
Tensiune nominala UL (Use Group C): 24; V
Curent nominal UL (Use Group C): 15; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group C): 24; V
Curent nominal CSA (Use Group C): 10; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 1 mm²;
Solid conductor: 0.14 … 1.5 mm² / 24 … 16 AWG;
Solid conductor; push-in termination: 0.5 … 1.5 mm² / 20 … 16 AWG;
Fine-stranded conductor: 0.14 … 1.5 mm² / 24 … 16 AWG;
Fine-stranded conductor; with insulated ferrule: 0.5 … 0.75 mm² / 20 … 18 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0.5 … 0.75 mm² / 20 … 18 AWG;
Strip length: 9 … 11 mm / 0.35 … 0.43 inch;
Numar total de conexiuni: 8;
Total number of potentials: 4;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross

section can also be inserted via push-in termination.;
Latime: 7 mm / 0.276 inch;
Inaltime from upper-edge of DIN-rail: 52.4 mm / 2.063 inch;
Adancime: 81.1 mm / 3.193 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 16,8; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143452915;
Customs tariff number: 85369010000;
Pret: 75,87 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/3-conductor-actuator-supply-terminal-block-led-yellow-for-pnp-high-side-switching-actuators-with-ground-connection-via-push-in-type-jumper-bars-1-mm2-push-in-cage-clamp-1-00-mm2-gray-151669