



**WAGO GROUND CONDUCTOR DISCONNECT TERMINAL BLOCK; WITH TEST
OPTION; WITH ORANGE DISCONNECT LINK; 120 V; 6 MM²; PUSH-IN CAGE
CLAMP®; 6,00 MM²; GRAY**

Operation status indicator: 120 V;

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Operating tool;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm²;

Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Solid conductor; push-in termination: 2,5 ... 10 mm² / 14 ... 8 AWG;

Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 2,5 ... 6 mm² / 16 ... 10 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 2,5 ... 6 mm² / 16 ... 10 AWG;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;

Numar total de conexiuni: 4;

Total number of potentials: 2;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Number of jumper slots: 1;

Latime: 15 mm / 0.591 inch;

Inaltime from upper-edge of DIN-rail: 36,8 mm / 1.449 inch;

Adancime: 96,3 mm / 3.791 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 42,4; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454789879;
Customs tariff number: 85365080900;
Pret: 195,87 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/ground-conductor-disconnect-terminal-block-with-test-option-with-orange-disconnect-link-120-v-6-mm2-push-in-cage-clamp-6-00-mm2-gray-151807>