



WAGO 3-WAY DISTRIBUTION CONNECTOR; 5-POLE; COD. P; 1 INPUT; 3 OUTPUTS;
RED

Note on Contact Resistance: approx. 1 m Ω of contact resistance approx. 0.25 m Ω contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 25; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 23; A

Numar poli: 5;

Total number of potentials: 5;

Ground function: with preceding ground contact;

Distanta intre pini: 10 mm / 0.394 inch;

Latime: 50 mm / 1.969 inch;

Inaltime: 36,7 mm / 1.445 inch;

Adancime: 46 mm / 1.811 inch;

Coding: P;

Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);

Number of mating cycles: ?200, without resistive load 100, with resistive load $I_N = 25$ A, tested (4 mm²/AWG 12);

Distributor type: Distribution connector, 3-way,;

Marking: N ? L1 L2 L3;

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily

accessible areas).;

Potential marking: N ? L1 L2 L3;

Application: Computer applications (UPS);

Tip contact (pluggable connector): Socket/plug;

Mismating protection: Yes;

Locking of plug-in connection: locking lever;

Locking lever: yes;

Culoare: red;

Material izolator: Polyamide 66 (PA 66);

Contact material: Copper or copper alloy (surface-treated);

Fire load: 0,655; MJ

Greutate: 41,7; g

Processing temperature: -5 ... +40 °C;

Continuous operating temperature: -35 ... +85 °C;

Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;

Product Group: 20 (WINSTA);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4045454945268;

Customs tariff number: 85366990990;

Pret: 80,81 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-way-distribution-connector-5-pole-cod-p-1-input-3-outputs-red-151821>