



WAGO 4-CONDUCTOR CHASSIS-MOUNT TERMINAL STRIP; SUITABLE FOR EX E II APPLICATIONS; 2-POLE; L1-N; WITHOUT GROUND CONTACT; FOR SELF-TAPPING SCREW 2.9 MM Ø FROM BELLOW; WITH 2X PIN; 4 MM²; 4,00 MM²; BLACK

Tensiune nominala EN (Ex e II): 440; V

Curent nominal (Ex e II): 28; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Operating tool; Push-button;

Connectable conductor materials: Copper;

Solid conductor: 0,5 ... 4 mm² / 20 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Stranded conductor: 0,5 ... 4 mm² / 20 ... 12 AWG;

Fine-stranded conductor: 0,5 ... 4 mm² / 20 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 0,5 ... 2,5 mm² / 20 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0,75 mm² / 18 AWG;

Strip length: 10 ... 11 mm / 0.39 ... 0.43 inch;

Numar poli: 2;

Numar total de conexiuni: 8;

Total number of potentials: 2;

Wiring type: Side-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Distanta intre pini: 12 mm / 0.472 inch;

Latime: 24 mm / 0.945 inch;

Inaltime de la fata: 22,3 mm / 0.878 inch;

Adancime: 35 mm / 1.378 inch;

Tip montaj: Screw mounting;

Marking: L1-N;

Culoare: black;

Fire load: 0,263; MJ
Greutate: 14,1; g
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4045454804091;
Customs tariff number: 85369010000;
Pret: 18,44 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-chassis-mount-terminal-strip-suitable-for-ex-e-ii-applications-2-pole-11-n-without-ground-contact-for-self-tapping-screw-2-9-mm-oe-from-bellow-with-2x-pin-4-mm2-4-00-mm2-black-151860>