



WAGO DOUBLE-DECK TERMINAL BLOCK; WITH PUSH-BUTTON; 4-CONDUCTOR THROUGH TERMINAL BLOCK; L; WITHOUT MARKER CARRIER; SUITABLE FOR EX E II APPLICATIONS; INTERNAL COMMONING; CONDUCTOR ENTRY WITH VIOLET MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; PUSH-IN CA

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Number of connection points (connection type): 2;

Tip actionare: Push-button;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Number of connection points: 2;

Numar total de conexiuni: 4;

Total number of potentials: 2;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 5,2 mm / 0.205 inch;

Inaltime from upper-edge of DIN-rail: 71,7 mm / 2.035 inch;
Adancime: 92,5 mm / 3.642 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Potential marking: L;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,005; MJ
Greutate: 13,2; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143844635;
Customs tariff number: 85369010000;
Pret: 16,73 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/double-deck-terminal-block-with-push-button-4-conductor-through-terminal-block-l-without-marker-carrier-suitable-for-ex-e-ii-applications-internal-commoning-conductor-entry-with-violet-marking-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2>