



WAGO DOUBLE-DECK TERMINAL BLOCK; 4-CONDUCTOR GROUND TERMINAL BLOCK; PE; WITH MARKER CARRIER; INTERNAL COMMONING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2,5 MM²; PUSH-IN CAGE CLAMP®; 2,50 MM²; GREEN-YELLOW

Ratings per: IEC/EN 60947-7-2;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar total de conexiuni: 4;

Total number of potentials: 1;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Latime: 6,2 mm / 0.244 inch;

Inaltime from upper-edge of DIN-rail: 61,8 mm / 2.433 inch;

Adancime: 69,7 mm / 2.744 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Potential marking: PE;

Marking level: Center/side marking;

Culoare: green-yellow;

Material izolator: Polyamide 66 (PA 66);
Fire load: 0,311; MJ
Greutate: 17; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821299110;
Customs tariff number: 85369010000;
Pret: 33,27 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/double-deck-terminal-block-4-conductor-ground-terminal-block-pe-with-marker-carrier-internal-commoning-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-green-yellow-152088>