



WAGO 4-CONDUCTOR CHASSIS-MOUNT TERMINAL STRIP; 4-POLE; WITHOUT GROUND CONTACT; 1 SNAP-IN FOOT PER POLE; 4 MM²; 4,00 MM²; BLACK

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Operating tool; Push-button;

Connectable conductor materials: Copper;

Solid conductor: 0.5 ... 4 mm² / 20 ... 12 AWG;

Solid conductor; push-in termination: 0.75 ... 4 mm² / 18 ... 12 AWG;

Stranded conductor: 0.5 ... 4 mm² / 20 ... 12 AWG;

Fine-stranded conductor: 0.5 ... 4 mm² / 20 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 0.5 ... 2.5 mm² / 20 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0.75 mm² / 18 AWG;

Strip length: 10 ... 11 mm / 0.39 ... 0.43 inch;

Numar poli: 4;

Numar total de conexiuni: 16;

Total number of potentials: 4;

Wiring type: Side-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Distanta intre pini: 12 mm / 0.472 inch;

Latime: 48 mm / 1.89 inch;

Inaltime de la fata: 22.3 mm / 0.878 inch;

Adancime: 35 mm / 1.378 inch;

Tip montaj: Snap-in mounting foot;

Marking: plain;

Culoare: black;
Fire load: 0,509; MJ
Greutate: 28; g
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4044918509121;
Customs tariff number: 85369010000;
Pret: 18,20 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-chassis-mount-terminal-strip-4-pole-without-ground-contact-1-snap-in-foot-per-pole-4-mm2-4-00-mm2-black-152143>