



WAGO POWER SUPPLY CONNECTOR

Tensiune nominala (III/2): 400; V
Tensiune nominala de supratensiune (III/2): 4; kV
Curent nominal: 18; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Tehnologie conexiune: PUSH WIRE®;
Solid conductor: 0,5 ... 1,5 mm² / 20 ... 16 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar poli: 5;
Solid conductor 2: 0,5 ... 2,5 mm² / 20 ... 14 AWG;
Numar total de conexiuni: 20;
Total number of potentials: 5;
Numar tipuri de conexiuni: 1;
Latime: 48,5 mm / 1.909 inch;
Inaltime: 19 mm / 0.748 inch;
Adancime: 24,5 mm / 0.965 inch;
Fire load: 0,261; MJ
Greutate: 15,4; g
Product Group: 8 (Misc. Chassis Mount Blocks);
Tip ambalare: bag;
Tara de origine: PL;
GTIN: 4044918397209;
Customs tariff number: 85369010000;
Pret: 13,66 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/power-supply-connector-152166>