



**PALAZZOLI RINO STAINLESS STEEL-GLASS LIGHTING FIXTURE 1X24W WITH  
ASYMMETRICAL REFLECTOR IN ALUMINIUM AND ELECTRONIC POWER SUPPLY  
230VAC/DC 50HZ G5 T5**

Puterea l?mpii: 1x24w

Tipul l?mpii: G5

Tip surs? de lumin?: T5

Dimensiuni: 690x200x100 mm

Indexul UGR:

Tipul gaurei: M20

Tipul de tratament: finisaje naturale

Temperatura camerei de depozitare min: -40 ° C

Temperatura camerei de depozitare max: + 70 ° C

Rezisten?a la ?oc: IK09 al doilea IEC / EN 62262

Sec?iunea de conductor Max: 2,5 mm<sup>2</sup>

Clasa de coroziune: C4 (ISO 9223)

Diametru de strangere: min 7 mm; Max 14 mm.

Frecven??: 50 / 60Hz

Tipul opticelor: reflector de aluminiu ultra luminos

Gradul de protec?ie: IP66 / IP67

Difuzor Tip: sticl? extraclear? de 4 mm

Unitate de alimentare: electronic?

Min. Amb. Temp.: -25 ° C

Max. Amb. Temp.: + 50 ° C

Tensiune de operare evaluat?: 220V-240V

Material de fabrica?ie: o?el inoxidabil AISI 304

Sistem de montare: fixare pe fund

Sistem de control / Dimming: Standard On-off

Pret: 1.825,11 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/rino-stainless-steel-glass-lighting-fixture-1x24w-with-asymmetrical-reflector-in-aluminium-and-electronic-power-supply-230vac-dc-50hz-g5-t5-190404>