



SCAME STECHER 16A 3P+N+E 3H 380V 50HZ / 440V 60HZ 50HZ 60HZ II 2GD
TERMINAL CU SURUB LOW TEMPERATURE [-50°C]

Seria comercial? - OPTIMA-EX [GD] serie

Descrierea sintetic? - Stecher

Versiune de montare - portabil?

Current nominal - 16A

Polonezi - 3p + n + E

Ora pozi?iei - 3h

Tensiune nominal? (interval) - 250-400V

Tensiune nominal? - 380V 50Hz / 440V 60Hz

Frecven?a de lucru - 50Hz

60hz.

Culoare - ro?u

Material - termoplastic

Gradul de protec?ie - Dovada Splash

Gradul de protec?ie IP - IP66

Tipuri de ie?iri disponibile - drepte

Terminale - Terminale cu ?uruburi

Material de contact - Cuzn (alam?)

Tratament de suprafa?? Contacte - Nickel-placat

Intrare cablu - Gland? prin cablu

Grup ?i categorii EX - II 2GD

Temperatura ambiant? TA Min - -50 ° C

Temperatura ambiantal? TA Max - 60 ° C

Op?iuni - Temperatur? sc?zut? [-50 ° C]

Pret: 511,94 LEI (TVA inclus)

Detalii online: [https://www.materialelectrice.ro/stecher-16a-3p-n-e-3h-380v-50hz-440v-60hz-50hz-60hz-ii-2gd-terminal-cu-surub-low-temperature-\[-50c\]](https://www.materialelectrice.ro/stecher-16a-3p-n-e-3h-380v-50hz-440v-60hz-50hz-60hz-ii-2gd-terminal-cu-surub-low-temperature-[-50c])

