



**GEWISS Q-DIN 5 ACS - MOBILE-PORTABLE - WITH CABLE AND PLUG - 3 3P+E 16A**  
**IEC309 - IP44**

Tip - Q-DIN 5 ACS

tip plac? - Cablat

Dim. exterioare LxHxP (mm) - 105x430x96

Greutate (Kg) - 4

Conformitate cu standardele - EN 61439-4 (ASC)

Caracteristici - Rezisten?? UV (EN 62208)

Clas? de protec?ie IP - IP65

Cod IK - IK09

Glow test conductori - 650 °C

Termo-presiune cu bil? - 70 °C

Clas? izola?ie - II

Surs? de alimentare - Fi?? mobil? 2P+E 16 A

Nr. poli - 3P+N+T

Putere prevazut?/alimentare - 8

Intrerup?tor general - RCBO 16A 4P 6 kA 0,03 A - tip c.a.

Protec?ie circuite - RCBO

Nr. prize - 3

Priz? 3P+T 16A - IEC 309 - 3

Lungime cablu - 4 m

Electrocod - 139

Ware number - 85371098

Pret: 1.491,40 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/q-din-5-acs-mobile-portable-with-cable-and-plug-3-3p-e-16a-iec309-ip44-211786>