



GEWISS COMPACT SIGURANTA AUTOMATA - MTC 45 - 3P CHARACTERISTIC C 20A **- 2MODULE**

Descriere - INTRERUP?TOR MAGNETOTERMIC COMPACT

Cod - MTC 45

Nr. poli - 3P

N. module - 2

Curent nominal - 20 A

Arc - C

Tensiune nominal? - 230-400 V

Standard - EN 60898, EN 60947-2

Frecven?? nominal? (Hz) - 50/60 Hz

Capacitate de intrerupere EN 60898 230V (Icn) - 4500 A

Capacitate de intrerupere EN 60898 400V (Icn) - 4500 A

Capacitate de intrerupere EN 60898 (Ics) - 1 x Icn

Capacitate de intrerupere EN 60947-2 230V (Icu) - 6 kA

Capacitate de intrerupere EN 60947-2 400V (Icu) - 4.5 kA

Capacitate de intrerupere EN 60947-2 (Ics) - 100% Icu

Tensiune de izolare - 500 V

Tensiune nominal? de rezisten?? la impulsuri - 4 kV

Tensiune minim? de operare - 12V ac/dc

Tensiune maxim? de operare - 440V AC / 220V DC

Rezisten?? electric? - 10000

Rezisten?? mecanic? - 20.000

Cablu cu sec?iune rigid? - <=1x16 - <=1x10+1x6 mm²

Cablu cu sec?iune flexibil? - <=1x10 - <=2x6 mm²

Cuplu de strangere nominal - 1,2 Nm

Temperatur? de operare - -25 +60 °C

Temperatur? de stocare - -40 +70 °C

Electrocod - 1411

Ware number - 85362010

Pret: 125,53 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/compact-siguranta-automata-mtc-45-3p-characteristic-c-20a-2module-212561>