



GEWISS COMPACT INTRERUPATOR DIFERENTIALCU PROTECTIE LA SUPRACURENT - MDC 45 - 3P CURBA C 16A TYPE AC IDN=0,3A - 3 MODULE

Descriere - INTRERUPATOR MAGNETOTERMIC DIFERENTIAL

Cod - MDC 45

Nr. poli - 3P

N. module - 3

Curent nominal - 16 A

Curent eronat m?surare - 300 mA

Tip - AC

Arc - C

Tensiune nominal? (EN/IEC 61009-1, 61009-2-1) - 400/415 V

Standard - IEC/EN 61009-1, IEC/EN 61009-2-1

Frecven?? nominal? (Hz) - 50/60 Hz

Capacitate de intrerupere EN 61009-1 400V (Icn) - 4500 A

Capacitate de intrerupere EN 61009-1 (Ics) - 1 x Icn

Capacitate de intrerupere EN 60947-2 400V (Icu) - 4.5 kA

Capacitate de intrerupere EN 60947-2 (Ics) - 100% Icu

Tensiune de izolare - 500 V

Nivel de imunitate (8/20 μ s) - 250 A

Tensiune nominal? de rezisten?? la impulsuri - 4 kV

Categorie supratensiune - III

Rezisten?? electric? - 10000

Rezisten?? mecanic? - 20.000

Cablu cu sec?iune rigid? - $\leq 1 \times 35$ - $\leq 2 \times 16$ - $\leq 1 \times 16 + 2 \times 10$ mm²

Cablu cu sec?iune flexibil? - $\leq 1 \times 35$ - $\leq 2 \times 16$ - $\leq 1 \times 16 + 2 \times 10$ mm²

Conexiune dubl? - DA (numai in aval)

Cuplu de strangere nominal - 2 Nm

Temperatur? de operare - -25 +40 °C

Temperatur? de stocare - -40 +70 °C

Compatibilitate auxiliare - Da

Pozi?ie montare - Oricare

Ware number - 85362010

Pret: 591,46 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/compact-intrerupator-diferentialcu-protectie-la-supracurent-mdc-45-3p-curve-c-16a-type-ac-idn-0-3a-3-module-213094>