



### GEWISS P-COMFORT - LOAD MANAGEMENT RELAY - WIRE VERSION

Descriere - Load management relay p-comfort

Model - Wire version

Tensiune nominal? (V) - 230 c.a.

Nr. module EN 50022 - 2

Curent nominal - 32 A

Tip Contact cu releu - Changeover (potential free contact)

capacitate Contact cu releu - 16 A AC1 250 V

Standard - EN 60669-1, EN 60669-2-1

Frecven?? nominal? (Hz) - 50

Tensiune de izolare - 1000 V

Tensiune nominal? de rezisten?? la impulsuri - 1 kV

Cablu cu sec?iune rigid? - Max 6 mm<sup>2</sup>

Cablu cu sec?iune flexibil? - Max 4 mm<sup>2</sup>

Rigid cable section for contact terminals - Max 4 mm<sup>2</sup>

Flexible cable section for contact terminals - Max 2,5 mm<sup>2</sup>

Temperatur? de operare - -5 +45 °C

Temperatur? de stocare - -25 +70 °C

Absorbed power with In - 2 VA

Sound level at 10 cm - 85 Db

Dimensiuni m?surate - Active power (absorbed and supplied), active energy (absorbed and supplied)

Resetting of energy count - Da

Acoustic warning threshold exceeded - Da

Adjustment power range - 0 ÷ 8 kW (3,8 kW default)

Adjustment of non-priority load contact opening delay time - 10 ÷ 120 s (45 s default)

Adjustment of non-priority load contact opening time - 10 ÷ 255 s (90 s default)

Electrocod - 140

Ware number - 85389099

Pret: 332,06 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/p-comfort-load-management-relay-wire-version-214580>