www.MATERIALE ELECTRICE.ro
Consiliere specializata



GEWISS LAMPA PROIECTOR TIP ELIA FL - STAND ALONE - XL2 - ASYMMETRICAL OPTIC - CRI 80 4000 K - IP66 - CLASS I - BLACK

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Industry, Logistic, Facade, Sport
Optic? - Asimetric
Luminaire - LED luminaire with small,mid and high lumen power
Unified Glare Rating - ULOR = 0%
Aplica?ie - Intern / Extern
Lumin? ie?ire (lm) - 26000
Unique digital code (Datamatrix) - Currently not present
Efficiency
(lm/W) - 130
Culoare - Negru
Culoare Temperatur? - 4000 K
Tip surs? de lumin? - LED - Neinlocuibil
Color Rendering Index - CRI 80
Puterea sistemului - 200 W
Standard Deviation Colour Matching - SDCM = 5
LED Lifetime - L80B50 (Tq25°) = 89.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 6.3
Standard - -
Garan?ie - 5 ani
ELETRICAL AND LIGHTING FEATURES - -
Temperatur? de stocare - -40° +85°
Tensiune de alimentare - 100-240 V
Operating temperature - -30° +50°

Frecven?? nominal? (Hz) - 50 / 60
MATERIALS - -
Driver - Included
Body - Aluminiu turnat
Driver failure rate - F05 = 81.000h Tq 25°C
Ecran - Flat silked tempered glass 4mm thick with Gewiss logo
Overvoltage protection - Overvoltage protection 10-6kV
Optic - With high efficiency optic system
Control System - PORNIT OPRIT
Gasket - -
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mouting and installation - Ceiling - Wall - Floor
External screw - O?el
Tilt - With adjustable bracket assembled
Colour - Powder coating
Wiring - With power cable
STANDARDS AND APPROVALS - -
Prindere - -
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperatur? la suprafa?? redus? - -
LED Maintenance - Not available
Certificare DIN 18032-3 - -
Driver Box - Integrat
IPEA - -
Suprafa?? maxim? expus? la vant - 0,15 m²
Clas? izola?ie - I
- - -
Clas? de protec?ie IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - 750 °C
- - -
Ware number - 94054010
Pret: 1.873,70 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lampa-proiector-tip-elia-fl-stand-alone-xl2-asymmetrical-optic-cri-80-4000-k-ip66-class-i-black-215038