



GEWISS CORP DE ILUMINAT PLAFONIERA TIP ELIA CL - STAND ALONE
EMERGENCY SENSOR - M2 - OPAL DIFFUSED OPTIC - CRI 80 4000 K - IP20/IP54 -
CLASS II - WHITE

GENERAL INFORMATION - -

OPTIC AND ILLUMINATING FEATURES - -

Context - Office, Stairs and technical rooms

Optic? - Wide opal

Luminaire - LED luminaire for diffuse light with emergency and motion sensor

Unified Glare Rating - -

Aplica?ie - Intern?

Lumin? ie?ire (lm) - 2550

Unique digital code (Datamatrix) - Currently not present

Efficiency

(lm/W) - 102

Culoare - Alb

Culoare Temperatur? - 4000 K

Tip surs? de lumin? - LED - Neinlocuibil

Color Rendering Index - CRI 80

Puterea sistemului - 25 W

Standard Deviation Colour Matching - SDCM = 3

LED Lifetime - L80B50 (Tq25°) = 50.000h

Photobiological Risk Class - RG0

Greutate (Kg) - 0.9

Standard - -

Garan?ie - 3 ani

ELETRICAL AND LIGHTING FEATURES - -

Temperatur? de stocare - -20° +65°

Tensiune de alimentare - 220-240 V

Operating temperature - -0° +45°

Frecven?? nominal? (Hz) - 50 / 60

MATERIALS - -

Driver - Included

Body - Polycarbonate

Driver failure rate - F025 = 50.000h Tq 25°C

Ecran - Polycarbonate

Overvoltage protection - Overvoltage protection 1kV

Optic - -

Control System - PORNIT OPRIT

Gasket - -

INSTALLATION AND MAINTENANCE - -

Locking Hook - -

Mouting and installation - Ceiling - Wall

External screw - -

Tilt - -

Colour - PC coloured

Wiring - With connection terminal

STANDARDS AND APPROVALS - -

Prindere - -

Clasificare - -

Optic Maintenance - Not available

Dispozitiv cu temperatur? la suprafa?? redus? - -

LED Maintenance - Not available

Certificare DIN 18032-3 - -

Driver Box - Integrat

IPEA - -

Suprafa?? maxim? expus? la vant - -

Clas? izola?ie - II

- - -

Clas? de protec?ie IP - IP20 - IP54

- - -

Cod IK - IK08

- - -

Glow Test conductori - 750 °C

- - -

Ware number - 94051098

Pret: 671,17 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/corp-de-iluminat-plafoniera-tip-elia-cl-stand-alone-emergency-sensor-m2-opal-diffused-optic-cri-80-4000-k-ip20-ip54-class-ii-white-215056>