www.MATERIALE ELECTRICE.ro
Consiliere specializata



GEWISS PROIECTOR LED TIP SMART [PRO] 2.0 - 1 MODUL - DIMABIL 1-10 V - ASYMMETRICAL A2 - 5700K (CRI 80) - IP66 - PROTECTION CLASS I

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Sport, Big Areas
Optic? - A2 - Asymmetrical Medium
Luminaire - LED luminaire with small,mid and high lumen power
Unified Glare Rating - G*3 - ULOR = 0
Aplica?ie - Intern / Extern
Lumin? ie?ire (lm) - 15300
Unique digital code (Datamatrix) - Currently not present
Efficiency
(lm/W) - 93
Culoare - Gri grafit
Culoare Temperatur? - 5700 K
Tip surs? de lumin? - LED - Neinlocuibil
Color Rendering Index - CRI>80
Puterea sistemului - 165 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)=50.000h; L80B10(Tq25°C)=110.000h
Photobiological Risk Class - -
Greutate (Kg) - 5.7
Standard - EN60598-1; EN60598-2-5; EN60598-2-24; IEC 62778; IEC62471; EN13201
Garan?ie - 5 ani
ELETRICAL AND LIGHTING FEATURES - -
Temperatur? de stocare - -
Tensiune de alimentare - 220 - 240 V
Operating temperature - -30 +40 °C

Frecven?? nominal? (Hz) - 50 / 60
MATERIALS - -
Driver - Included
Body - Aluminiu turnat
Driver failure rate - F10 = 100.000h Tq25°C
Ecran - Flat tempered glass 4mm
Overvoltage protection - DM 6 kV / CM 10 kV
Optic - Polished anodised aluminum reflector with 99.99% pure aluminum
Control System - Autonom - 1/10V
Gasket - Anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - Hexagonal metric screws
Mouting and installation - High-mast lighting - Wall mounting - Ground mouting
External screw - Stainless steel
Tilt - Rotation on bracket with integrated goniometer
Colour - Polyester powder coated
Wiring - Watertight connector
STANDARDS AND APPROVALS - -
Prindere - Consol?
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperatur? la suprafa?? redus? - Da
LED Maintenance - Not available
Certificare DIN 18032-3 - Da
Driver Box - Integrat
IPEA - -
Suprafa?? maxim? expus? la vant - 0,085 m2
Clas? izola?ie - I
- - -
Clas? de protec?ie IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - -
- - -
Ware number - 94054010
Pret: 2.286,69 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/proiector-led-tip-smart-pro-2-0-1-modul-dimabil-1-10-v-asymmetrical-a2-5700k-cri-80-ip66-protection-class-i-215420