www.MATERIALE ELECTRICE.ro
Consiliere specializata



GEWISS LAMPA STRADALA ROAD [5] - MINI - 1 (1X3 LED) - BIPOWER WITH SELF-LEARNING - WIDE OPTIC - 4000 K - 1A - IP66 - CLASS II

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Street and parking lighting
Optic? - WIDE
Luminaire - LED Road Equipment
Unified Glare Rating - G*3 - ULOR = 0
Aplica?ie - Exterior
Lumin? ie?ire (lm) - 4300
Unique digital code (Datamatrix) - Currently not present
Efficiency
(lm/W) - 110
Culoare - Gri grafit
Culoare Temperatur? - 4000 K
Tip surs? de lumin? - LED - Neinlocuibil
Color Rendering Index - CRI>70
System
power - 39 W @ 1A
Standard Deviation Colour Matching - SDCM = 5
LED Lifetime - L90B10(Tq25°C)>115.000h; L90B10(Tq40°C)=115.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 6.4
Standard - EN 60598-2-3, EN 60598-1 IEC/TR 62778
Garan?ie - 5 ani
ELETRICAL AND LIGHTING FEATURES - -
Temperatur? de stocare - -
Tensiune de alimentare - 220 - 240 V

Operating temperature - -25 +40 °C
Frecven?? nominal? (Hz) - 50 / 60
MATERIALS - -
Driver failure rate - F10=100.000h Tq25°C/75.000h Tq40°C
Body - Aluminiu turnat
Driver - Included
Ecran - 4mm thick flat tempered glass
Overvoltage protection - DM 10KV / CM 10KV
Optic - Metallized polycarbonate reflector
Control System - Regim dual cu autoinv??are
Gasket - Anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - Integrated front handle
Mouting and installation - Pole Head - Outreach
External screw - O?el
Tilt - Console cu acces pe lateral?-20° ÷ +10° - -10° ÷ +20° cap de stalp
Colour - Powder coating
Wiring - Intrerup?tor sec?ionator
STANDARDS AND APPROVALS - -
Prindere - Pole Head - Outreach
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperatur? la suprafa?? redus? - -
LED Maintenance - Not available
Certificare DIN 18032-3 - -
Driver Box - Integrat
IPEA - -
Suprafa?? maxim? expus? la vant - 0,15 m²
Clas? izola?ie - II
- - -
Clas? de protec?ie IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - -
- - -
Ware number - 94054039
Pret: 1.865,65 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lampa-stradala-road-5-mini-1-1x3-led-bipower-with-self-learning-wide-optic-4000-k-1a-ip66-class-ii-215826