www.MATERIALE ELECTRICE.ro
Consiliere specializata



GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] - OPAL SHIELD - DALI - 800MM - 5700 K (CRI 80) - 220/240V 50/60HZ - IP66/IP69 - CLASS II

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Lighting of warehouses, indoor parking and industrial production rooms
Optic? - Wide opal
Luminaire - LED fixture for general lighting
Unified Glare Rating - UGR ? 25 (4H/8H)
Aplica?ie - Intern?
Lumin? ie?ire (lm) - 3200
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 119
Culoare - Grey (RAL 7035)
Culoare Temperatur? - 5700 K
Tip surs? de lumin? - LED - Neinlocuibil
Color Rendering Index - CRI>80
Puterea sistemului - 27 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)=45.000h; L80B10(Tq25°C)=92.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 1.5
Standard - EN60598-1; IEC 62778; IEC62471
Garan?ie - 5 ani
ELETRICAL AND LIGHTING FEATURES - -
Temperatur? de stocare - -25 +80 °C
Tensiune de alimentare - 220 - 240 V
Operating temperature - -25 +50 °C

Frecven?? nominal? (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - Polycarbonate
Driver failure rate - F10 = 100.000h Tq25°C
Ecran - UV stabilised polycarbonate
Overvoltage protection - DM 1KV / CM 2KV
Optic - Integrated in the screen
Control System - Stand Alone - DALI
Gasket - CNC deposited sealant
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mouting and installation - Ceiling - Wallmounting - Suspension
External screw - -
Tilt - With fixing bracket
Colour - RAL7035 colored PC paste
Wiring - With GW connect watertight connector
STANDARDS AND APPROVALS - -
Prindere - Stainless steel support
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperatur? la suprafa?? redus? - Da
LED Maintenance - Not available
Certificare DIN 18032-3 - Not available
Driver Box - Integrat
IPEA - -
Suprafa?? maxim? expus? la vant - -
Clas? izola?ie - II
- - -
Clas? de protec?ie IP - IP66/IP69
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051040
Pret: 458,30 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-opal-shield-dali-800mm-5700-k-cri-80-220-240v-50-60hz-ip66-ip69-class-ii-216288