www.MATERIALE ELECTRICE.ro
Consiliere specializata



GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] S - DISPERSOR TRANSPARENT - CONECTOR CONEXIUNE RAPIDA - STAND ALONE - 1600MM - 4000 K (CRI 80) - 220/240V 50/60HZ - IP66/IP69 - CLASS II

Aplica?ie - Intern?
Seria - SMART [3] SUPER
Tip - Autonom
Clas? de protec?ie IP - IP66/IP69
Cod IK - IK08
Clas? izola?ie - II
Glow Test conductori - 850 °C
Lungimea - 1600 mm
Dispozitiv cu temperatur? la suprafa?? redus? - Conform
Ecran - Transparent
Temperatur? de operare - -20 +35 °C
Greutate (Kg) - 2.5
Tensiune - 220/240 V - 50/60 Hz - Autonom
Lampa tip - LED
Tip driver - LED driver de curent constant
Puterea sistemului - 67 W
Tip surs? de lumin? - LED - Neinlocuibil
Temperatur? de culoare - 4000 K (CRI>80)
Clas? de eficien?? a LED-urilor integrate - A ÷ A++
Flux nominal (lm) - 8600
Lumin? ie?ire (lm) - 8200
LED Life Time (L80B50) - 90000 h
Durat? utilizare LED L80B20 - 70000 h
Failure rate apparecchio (35.000h, Tq=35° C) - <10%
Failure rate apparecchio (50.000h, Tq=25° C) - <10%

Garan?ie - 3 ani
Overvoltage resistance - Common mode: 2KV; Differential mode: 1KV
Electrocod - 2434
Ware number - 94051040
Pret: 791,48 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-s-dispersor-transparent-conector-conexiune-rapida-stand-alone-1600mm-4000-k-cri-80-220-240v-50-60hz-ip66-ip69-class-ii-216416