www.MATERIALE ELECTRICE.ro
Consiliere specializata



GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] PLUS - 1600 - INTEGRATED EMERGENCY - DALI DT1 - 3H DT6 - 3000K - CRI>80

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Lighting of warehouses, indoor parking and industrial production rooms
Optic? - Microprismatic transparent
Luminaire - LED fixture for general lighting
Unified Glare Rating - UGR ? 25 (4H/4H)
Aplica?ie - Intern?
Lumen
output (lm) - 7100 (600 Em.)
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 129
Culoare - Gri RAL 7035
Culoare Temperatur? - 3000 K
Tip surs? de lumin? - LED - Neinlocuibil
Color Rendering Index - CRI>80
System
power - 50W (+5W Emerg.)
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)=50.000h; L80B10(Tq25°C)=100.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 4.2
Standard - EN60598-1; IEC 62778; IEC62471; 60598-2-22
Garan?ie - 5 ani
ELETRICAL AND LIGHTING FEATURES - -
Temperatur? de stocare - -15°C ÷ +25°C

Tensiune de alimentare - 220 - 240 V
Operating temperature - +5°C ÷ +40 °C
Frecven?? nominal? (Hz) - 50 / 60
MATERIALS - -
Driver - Included
Body - Polycarbonate
Driver failure rate - F10 = 100.000h Tq25°C
Ecran - UV stabilised polycarbonate
Overvoltage protection - DM 1KV / CM 2KV
Optic - Integrated in the screen
Control System - 1 x DALI DT6 + 1 x DALI DT1 (Emerg. 3h)
Gasket - CNC deposited sealant
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mouting and installation - Ceiling - Wallmounting - Suspension
External screw - -
Tilt - With fixing bracket
Colour - RAL7035 colored PC paste
Wiring - With GW connect watertight connector
STANDARDS AND APPROVALS - -
Prindere - Stainless steel support
Clasificare - KITE MARK (Emergency KIT)
Optic Maintenance - Not available
Dispozitiv cu temperatur? la suprafa?? redus? - Da
LED Maintenance - Only for LiFePO battery
Certificare DIN 18032-3 - -
Driver Box - Integrat
IPEA - -
Suprafa?? maxim? expus? la vant - -
Clas? izola?ie - II
- - -
Clas? de protec?ie IP - IP65
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051040
Pret: 1.564,89 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-plus-1600-integrated-emergency-dali-dt1-3h-dt6-3000k-cri-80-216562