www.MATERIALE ELECTRICE.ro
Consiliere specializata



GEWISS CORP DE ILUMINAT CU LED SMART [4] - HLO - 1 MODUL - THROUGH WIRING - 1 X DALI DT6 - ASYMMETRICAL OPTIC - 4000 K - IP66 - CLASS I

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Logistics and industrial manufacturing lighting
Optic? - Asimetric
Luminaire - LED Industrial Reflector
Unified Glare Rating - -
Aplica?ie - Intern?
Lumin? ie?ire (lm) - 8200
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 128
Culoare - Gri RAL 7035
Culoare Temperatur? - 4000 K
Tip surs? de lumin? - LED - Neinlocuibil
Color Rendering Index - CRI>80
Puterea sistemului - 64 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)>150.000h; L90B10(Tq50°C)=100.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 3.5
Standard - EN 60598-1 ; EN 60598-2-1 ; EN 60598-2-24
Garan?ie - 5 ani
ELETRICAL AND LIGHTING FEATURES - -
Temperatur? de stocare - -40 +70 °C
Tensiune de alimentare - 220 - 240 V
Operating temperature - -30°C ÷ +50 °C

Frecven?? nominal? (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - PA6 "Halogen Free" loaded fibreglass
Driver failure rate - F10 = 100.000h Tq25°C/50.000h Tq50°C
Ecran - Tempered glass Thickness 4mm
Overvoltage protection - DM 6 kV / CM 10 kV
Optic - Metallic PC reflector and PMMA lenses
Control System - 1 x DALI DT6
Gasket - anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mouting and installation - Ceiling - Wallmounting - Suspension
External screw - O?el
Tilt - With bracket accessory
Colour - Gri RAL 7035
Wiring - With GW connect watertight connector
STANDARDS AND APPROVALS - -
Prindere - -
Clasificare - -
Optic Maintenance - Non-replaceable
Dispozitiv cu temperatur? la suprafa?? redus? - Da
LED Maintenance - Non-replaceable
Certificare DIN 18032-3 - With Bracket - Rope Kit + terminal (in approval)
Driver Box - Integrat
IPEA - -
Suprafa?? maxim? expus? la vant - 0,097 m²
Clas? izola?ie - I
- - -
Clas? de protec?ie IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051098
Pret: 1.298,86 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/corp-de-iluminat-cu-led-smart-4-hlo-1-modul-through-wiring-1-x-dali-dt6-asymmetrical-optic-4000-k-ip66-class-i-216804