www.MATERIALE ELECTRICE.ro
Consiliere specializata



GEWISS CORP DE ILUMINAT CU LED SMART [4] - UL -2 MODULE - STAND ALONE - ON / OFF - ARRAY OPTIC - 4000 K - IP66 - CLASS I

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Logistics and industrial manufacturing lighting
Optic? - Array
Luminaire - LED Industrial Reflector
Unified Glare Rating - UGR ? 25
Aplica?ie - Intern?
Lumin? ie?ire (lm) - 17500
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 136
Culoare - Gri RAL 7035
Culoare Temperatur? - 4000 K
Tip surs? de lumin? - LED - Neinlocuibil
Color Rendering Index - CRI>80
Puterea sistemului - 129 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)>150.000h; L90B10(Tq40°C)=140.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 6.5
Standard - UL 1598 - CSA C22.2 No. 250.0-18
Garan?ie - 5 ani
ELETRICAL AND LIGHTING FEATURES - -
Temperatur? de stocare - -
Tensiune de alimentare - 120-277 V
Operating temperature - -25°C ÷ +40 °C

Frecven?? nominal? (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - PA6 "Halogen Free" loaded fibreglass
Driver failure rate - F10=100.000h Tq25°C/50.000h Tq40°C
Ecran - Tempered glass Thickness 4mm
Overvoltage protection - DM 6 kV / CM 10 kV
Optic - Metallized polycarbonate reflector
Control System - ON / OFF
Gasket - anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mouting and installation - Ceiling - Wallmounting - Suspension
External screw - O?el
Tilt - With bracket accessory
Colour - Gri RAL 7035
Wiring - Single wiring with anti-breathing cable exiting metallic PG (NO Connector)
STANDARDS AND APPROVALS - -
Prindere - -
Clasificare - -
Optic Maintenance - Non-replaceable
Dispozitiv cu temperatur? la suprafa?? redus? - Da
LED Maintenance - Non-replaceable
Certificare DIN 18032-3 - -
Driver Box - Integrat
IPEA - -
Suprafa?? maxim? expus? la vant - 0,184 m²
Clas? izola?ie - I
- - -
Clas? de protec?ie IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051098
Pret: 2.770,84 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/corp-de-iluminat-cu-led-smart-4-ul-2-module-stand-alone-on-off-array-optic-4000-k-ip66-class-i-216972