

GEWISS CORP DE ILUMINAT SUPENDAT PENTRU HALA ESALITE FL - 20K - ELLIPTICAL OPTIC - DALI - 3000 K (CRI 80) - IP66 - CLASS I - RAL 9006 GREY

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Industry, Logistic, Facade, Sport
Optic? - Eliptic
Luminaire - LED luminaire with mid and high lumen power
Unified Glare Rating - UGR ? 28
Aplica?ie - Intern / Extern
Lumin? ie?ire (lm) - 14700
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 99
Culoare - Gri RAL 9006
Culoare Temperatur? - 3000 K
Tip surs? de lumin? - LED - Neinlocuibil
Color Rendering Index - CRI>80
Puterea sistemului - 148 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10 (Tq 25°) 100000 h; L90B10 (Tq 50°) 55000 h
Photobiological Risk Class - -
Greutate (Kg) - 9.5
Standard - EN60598-1; EN60598-2-5; IEC 62778; IEC62471
Garan?ie - 5 ani
ELETRICAL AND LIGHTING FEATURES - -
Temperatur? de stocare - -25°C ÷ +70°C / HR 10% ÷ 85%
Tensiune de alimentare - 220-240 V
Operating temperature - -25°C ÷ +40 °C

Frecven?? nominal? (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - Aluminiu turnat
Driver failure rate - F10 = 100.000h Tq25°C/50.000h Tq50°C
Ecran - Flat tempered glass 4mm
Overvoltage protection - DM 6KV / CM 8KV
Optic - PMMA lens
Control System - DALI
Gasket - CNC deposited sealant
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mouting and installation - Consol?
External screw - Stainless steel
Tilt - With graduated fixing bracket
Colour - Polyester powder coated
Wiring - With watertight connector
STANDARDS AND APPROVALS - -
Prindere - -
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperatur? la suprafa?? redus? - -
LED Maintenance - Not available
Certificare DIN 18032-3 - Nu
Driver Box - Integrat
IPEA - -
Suprafa?? maxim? expus? la vant - 0,13 m²
Clas? izola?ie - I
- - -
Clas? de protec?ie IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - -
- - -
Ware number - 94054010
Pret: 2.876,41 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/corp-de-iluminat-supendat-pentru-hala-esalite-fl-20k-elliptical-optic-dali-3000-k-cri-80-ip66-class-i-ral-9006-grey-217422