



COMTEC MOTOR STARTER (FARA RELEU), LC1-D50 10, 50A/220V

DATE TEHNICE

Standard: EN 50298; EN 60529; EN 50274;

Putere motor (kw) in regim AC3 la tensiune: 230V-15; 400V- 22;

Temperatura mediului: -5C...+40C;

Anduranta: > 1500000 cicluri la I=ITH;

Tip constructiv: Marimile 1 si 2- policarbonat ignifugat; Marimea 3- metal;

Conductor racord: Identic cu cel de la contactoare in functie de marimea fiecaruia;

Montaj: Pe perete cu dibluri si holtsuruburi;

Borne de legatura: Cu surub si saiba profilata pentru doua conductoare;

Releu termic: Marimea 1 si 2 - LR2-D13...; Marimea 3 - LR2-D33...;

Reglajul domeniului: Marimea 1 si 2: 0.4-0.63; 0.63-1; 1-1.6; 1.6-2.5; 2.5-4; 4-6; 5.5-8; 7-10; 9-13; 12-18; 17-25; 25-32;

Marimea 3: 23-32; 37-50; 55-70; 63-80; 80-93;

Pret: 447,30 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/motor-starter-fara-releu-lc1-d50-10-50a-220v>